



## **INO CrimmBoss Electrical Crimper for insulated ferrules**

Insulated ferrules from **0,25 to 2,5 mm<sup>2</sup>** can be processed without tool change or any adjustments. Besides the ease of use are **flexibility** and **mobility** further features of the **INO CrimmBoss**. It works independently of its position (**standing, hanging or lying**) or the work area (machine, work bench, control boxes etc.) The result is a **simplified work process even under rough conditions**.



The patented design of the **INO CrimmBoss** prevents a faulty or a premature crimp action. Only if the ferrule is inserted entirely into the guide funnel does the mechanical contact trigger the electro-magnetic hammer.

### Specifications

Crimp Range :	0,14 - 1,0 mm <sup>2</sup>	<b>INO CrimmBoss 1</b>
	0,50 - 2,5 mm <sup>2</sup>	<b>INO CrimmBoss 0</b>
Crimp Length :	1 x 13 mm	
Cycle Time :	approx. 0,2 sec.	
Power Supply :	220/230V 50Hz	
Dimensions :	248 mm long	
Part Number :	60.10.00	<b>INO CrimmBoss 0</b>
	60.20.00	<b>INO CrimmBoss 1</b>

*The crimp quality is in accordance with DIN requirements*

## **INO AC 25/25T + 100/100T Pneumatic Crimper**

For crimp wire end sleeves quickly and without effort. The **INO AC 25** and **INO AC-100** is lightweight and easy to use. The crimping mechanism is easily activated, making it perfectly suited for work in control cabinets and electrical equipment. Table top versions of **INO AC-25T** and **INO AC-100T** are actuated by a foot switch, allowing the operator to use both hands. These versions are perfect for bench work such as cable assemblies. These tools are maintenance free – they require no routine calibration – only 60–90 psi to allow proper operation. With their rugged polyamide casings they are ideal for heavy duty use in industry.



**INO AC-25 Handtool**



**INO AC-25-T Table Top Version**



### Specifications

Crimp Range :	0,25 - 2,5 mm <sup>2</sup> / AWG 24-14	
Crimp Length :	max. 8 mm	
Dimensions :	<b>Handtool</b> Ø 44 x 200 mm	
Weight :	<b>Handtool</b> approx. 400 g	
Part Number :	82.05.0000	<b>INO AC-25</b>
	82.05.1000	<b>INO AC-25 T</b>

### **INO AC-100 + AC-100 T**

Crimp Range :	4,0 - 10 mm <sup>2</sup> / AWG 12-8	
Crimp Length :	max. 8 mm	
Dimensions :	<b>Table Top T</b> Ø 140 x 200 x 70 mm	
Weight :	<b>Table Top T</b> approx. 1000 g	
Part Number :	82.05.2000	<b>INO AC-100</b>
	82.05.3000	<b>INO AC-100 T</b>