

INO AM-015 Stripping Machine



Special characteristics

- Extremely short stranded wire ends can be processed (distance cover to stripping blades > 9 mm)
- Exact parallel guide of the blade heads
- Processing with die-blades, prismatic blades and flat stripping blades
- Blade change within seconds and without any tool
- Sensor release of the stripping process
- Self-centring clamping jaws
- Air blow - out (to avoid insulation slugs)

INO C-32-M Stripping Machine

Optimal stripping quality is guaranteed by digital display for diameter Setting up

- Digital display for stripping diameter
- New development: 4 Blade high mechanism, optimal stripping quality as rotary blade cutting
- Easily select full or partial strip
- Strippable from AWG12 to AWG32 by micrometer dial
- High speed cycle time at 0.3 sec
- Light and portable, easily transport



Specification

	<i>INO AM-015</i>	<i>INO C-32-M</i>
Wire Sizes	: from 0,15 up to 4,0 mm ²	from 0,03 up to 3,0 mm ²
Wire Insulation Diameter	: up to 5,0 mm	
Flat Cables, Width	: up to 8 mm	---
Strip Length	: 1,5 - 15 mm	1,5 - 25 mm
Semi Strip	: from 1- 5 mm	min. 1 mm
Cycle Time	: approx. 0,5 sec.	Approx. 9,3 sec.
Operating Pressure	: 3 - 6 bar	---
Air/Cycle (6 bar)	: approx. 0,15 l	---
Power Supply	: ---	100V to 240V
Dimensions, WxDxH	: 95 x 280 x 165 mm	85 x 350 x 160 mm
Weight	: 3,5 kg	4,5 kg
Part Number	: 39.15.00	41.03.00
<u>Accessories</u>	39.15.285004 maintenance unit, compl. installed	Gripper for special spec wire
	39.15.280063 flat stripping blades, pair	Foot switch
	39.15.280059.x die-blades, pair	Air blow-out kit
	39.15.282500.x double die-blades, pair	
	all blades with TIN	