

## ***INO CPG - Series* Crimping Machines**

The ***INO CPG - Series*** can be supplied in a bench version for foot pedal operation, or for automatic operation via a pulse from a lead maker. All presses have fully interlocking safety guards, are CE marked, and have industry standard 3 point fixing quick change mini-applicator base plates. They have a reel arm adjustable to rear feed or left hand side feed position, together with a guide plate to give easy terminal entry onto the applicator. They are calibrated to the standard shut height of 135,78 mm, which makes them suitable for all industry standard mini-applicators.

***INO CPG T-25 / 923* and *CPG T-50 / 925* for large terminals**

### **FEATURES**

- ***INO Stripper Crimper*** can be fitted - use for strip and crimp cables in one operation
- Adjustable Jog Length / Split Length / Brake Power
- Daily counter / total press cycle counter



***INO CPG T-12/921***



***INO CPG T-20/922***



**with *INO Stripper***

### **Specification**

|                      | <b><i>INO CPG T-12 / 921</i></b>           | <b><i>T-20 / 922</i></b>  | <b><i>T-25 / 923</i></b> | <b><i>T-50 / 925</i></b> |
|----------------------|--|---------------------------|--------------------------|--------------------------|
| Force of Pressure    | 12 kN                                      | 20 kN                     | 25 kN                    | 50 kN                    |
| Cross Sections Range | up to 4,0 mm <sup>2</sup>                  | up to 6,0 mm <sup>2</sup> | up to 10 mm <sup>2</sup> | up to 16 mm <sup>2</sup> |
| Electric Motor       | asynchronous type with worm gear box RA 40 |                           |                          |                          |
| Motor Power          | 0,37 kW                                    | 0,75 kW                   | 1,0 kW                   | 1,3 kW                   |
| Standard Stroke      | 40 mm                                      | 40 mm                     | 40 mm                    | 40 mm                    |
| Dimensions, mm       | 690x250x210                                | 690x290x260               | 780x290x260              | 890x290x260              |
| Weight               | 35 kg                                      | 65 kg                     | 85 kg                    | 105 kg                   |
| Part Number          | 23.921.00                                  | 23.922.00                 | 23.923.00                | 23.925.00                |